

NCR RealPOS™ Performance Touch Display

Looking for a high-performance touch display that's easy to use, flexible and durable?

YES

The NCR RealPOS Performance Touch Display maximizes store productivity and ensures the highest level of customer satisfaction

Designed for a variety of retail environments with a robust capacitive touch technology, this display provides superior usability and accuracy.

- **Durability to last in today's retail environment**

Increased resistance to common retail contaminants, such as dirt, grease, water, coffee, vinegar, cleaning detergents and gasoline. Utilizes dual-bulb backlight technology for longer life.

- **Protects your investment with open systems drive flexibility**

Whether you use Microsoft Windows® or Linux®, NCR's industry standard OPOS and JavaPOS driver support, teamed with industry standards for connectivity, will give you seamless integration.

- **Built tough to sustain real-world stress and the long hours of the retail world**

Comprehensive environmental and compatibility testing, along with strict manufacturing standards, provide you with confidence that your touch display will keep working despite mishaps at the checkout.



For more information, visit www.ncr.com,
or email retail@ncr.com.

Key Features

- Designed for NCR family look and feel
- Optional 3-track MSR (USB)
- Integrated stereo speakers
- VESA mount compliant
- Flashable firmware via USB

Why NCR?

With over 125 years of retail experience, NCR is a leading global provider of assisted- and self-service solutions. We help our clients around the world improve their customer interactions, implement change quickly and proactively, and transform their businesses to become leaders and change agents. We can help you, too.

Technical Specifications

DISPLAY

- Display type: 15" active matrix, high-bright color LCD
- Native resolution: XGA (1024 x 768)
- Resolutions supported: VGA, SVGA, SXGA
- Dual-bulb backlight
- Backlight life: 50,000 hours to half brightness
- Brightness with touch:
 - Capacitive: 315 typical
 - Contrast: 400:1

TOUCH TECHNOLOGY

- Capacitive

CONNECTIVITY

- Video interface: VGA or DVI
- Touch interface: USB
- Power: powered USB
- Additional ports: 2 x USB (2.0) ports

PHYSICAL SPECIFICATIONS

- Without mount (WxDxH):
14.5" x 2.25" x 13"
(368mm x 57.15mm x 330mm)
- With mount (WxDxH):
15.5" x 2.25" x 13.75"
(394mm x 57.15mm x 350mm)
- VESA mount compliant

COLORS

- Beige or charcoal

ENVIRONMENTAL SPECIFICATIONS

- Operating temperature: 41°F–113°F
(5°C–45°C)
- Operating humidity: 10%–90%



Experience a new world of interaction

NCR RealPOS Performance Touch Display

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR RealPOS is either registered trademark or trademark of NCR Corporation in the United States and/or other countries. All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders.